

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
3 July 2003 (03.07.2003)

PCT

(10) International Publication Number  
WO 03/055198 A2(51) International Patent Classification<sup>7</sup>:

H04N

(21) International Application Number: PCT/US02/40259

(22) International Filing Date:

18 December 2002 (18.12.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/342,045	19 December 2001 (19.12.2001)	US
60/342,179	19 December 2001 (19.12.2001)	US
60/342,189	19 December 2001 (19.12.2001)	US
60/342,188	19 December 2001 (19.12.2001)	US


(71) Applicant (for all designated States except US): ABB  
RESEARCH LTD. [CH/CH]; P.O. Box 8131, CH-8050  
Zurich (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): UY, David [US/US];  
5409 Tryon Road, Raleigh, NC 27606 (US). EMOND,  
Glen [US/US]; 1507 Lakeside Drive, Wilson, NC 27896  
(US). SUN, Shan, C. [US/US]; 3901 NW 101 Drive, Coral  
Springs, FL 33065 (US). HART, David, G. [US/US];  
2726 Blaydon Drive, Raleigh, NC 27606 (US). STOUPIS,  
James, D. [US/US]; 2600 Sterling Park Drive, Raleigh,  
NC 27603 (US). PETRIE, Edward, M. [US/US]; 407  
Whisperwood Drive, Cary, NC 27511 (US).(74) Agents: SAMUELS, Steven, B. et al.; Woodcock Wash-  
burn LLP, One Liberty Place, 46th Floor, Philadelphia, PA  
19103 (US).(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR MONITORING AND CONTROL OF FIELD ELECTRICAL POWER EQUIPMENT

(57) **Abstract:** A power facility has at least one power element and a system monitors/controls at least a portion of the power facility. In the system, a field drop is coupled to each element for monitoring same, reporting status data, receiving control information, and controlling such element. A local area network (LAN) couples each field drop to a hub, and a data server is coupled to the hub. The data server receives the status data from each field drop and takes any appropriate action necessary in response thereto, and also allows a user to access any particular field drop of the system to read data for the corresponding element and issue control commands for the element to be carried out by the corresponding field drop.



MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.